

Appl. No. 10/065, 005

Amendment dated January 18, 2005

Amendment made in response to Office Action dated October 18, 2004

### **Amendments to the Claims**

This listing of claims will replace all prior versions and listing of claims in the application:

### **Listings of Claims:**

1. (currently amended) An interface unit for communication between an integrated services digital network (ISDN) based bus and a processor bus, wherein data in the ISDN-based bus is transferred in ISDN frames divided into a plurality of slots comprising:

a data transfer unit ~~inleudes~~ includes

a processor bus interface coupled to a processor bus, the processor bus interface includes a processor buffer,

an ISDN bus interface coupled to an ISDN-based bus, the ISDN bus interface includes an ISDN buffer; and

a control unit coupled to the data transfer unit for controlling the transfer of data between the processor bus and ISDN-based bus,

wherein the interface unit is capable of accessing all slots in an ISDN frame.

2. (original) The interface unit of claim 1 wherein said processor bus interface is coupled to the ISDN-based bus interface via an interface buffer comprising a group of register banks, said group of register banks having a control input terminal.

3. (original) The interface unit of claim 2 wherein the control unit further comprises a register bank control unit coupled to the interface buffer for controlling the group of register banks.

Appl. No. 10/065, 005

Amendment dated January 18, 2005

Amendment made in response to Office Action dated October 18, 2004

4. (original) The interface unit of claim 1 wherein the ISDN buffer comprises at least one shift register for parallel/serial data conversion.

5. (original) The interface unit of claim 1 wherein the processor bus interconnects a central processing unit, a memory unit and peripheral devices.

6. (original) The interface unit of claim 5 wherein the ISDN-based bus comprises an ISDN-oriented modular bus for coupling to voice, data and/or video devices.

7. (original) The interface unit of claim 1 wherein said processor bus is connected to a high-speed data transfer unit.

8. (original) The interface unit of claim 7 wherein the high-speed data transfer unit is a Universal Serial Bus.

9. (new) An interface to facilitate communication between an ISDN-based bus which communicates in ISDN frames divided into a plurality of slots and a processor bus comprising:

a data transfer unit for buffering data that are to be transferred between the processor bus and ISDN-based bus; and

a control unit coupled to the data transfer unit for controlling the transfer of data between the processor bus and ISDN-based bus, wherein the interface is capable of accessing all slots of an ISDN frame.

Appl. No. 10/065, 005

Amendment dated January 18, 2005

Amendment made in response to Office Action dated October 18, 2004

10. (new) The interface of claim 9 wherein the control unit is programmed to determine the direction of data transfer and which slot or slots to access.
11. (new) The interface of claim 10 either operates in frame-based processing or in slot-based processing.
12. (new) The interface of claim 10 wherein the data transfer unit comprises a memory module for buffering data that are to be transferred between the processor bus and the ISDN-based bus.
13. (new) The interface of claim 12 either operates in frame-based processing or in slot-based processing.
14. (new) The interface of claim 9 wherein the data transfer unit comprises a memory module for buffering data that are to be transferred between the processor bus and the ISDN-based bus.
15. (new) The interface of claim 14 either operates in frame-based processing or in slot-based processing.
16. (new) The interface of claim 9 either operates in frame-based processing or in slot-based processing.
17. (new) The interface of claim 9 wherein the data transfer unit comprises:

Appl. No. 10/065, 005

Amendment dated January 18, 2005

Amendment made in response to Office Action dated October 18, 2004

processor bus interface storage (PBIS) block coupled to the processor bus, wherein the PBIS includes a PBIS memory unit for buffering data that are to be transferred to or received from the processor bus; and

ISDN-based bus interface storage (IBIS) block coupled to the ISDN-based bus, wherein the IBIS includes an IBIS memory unit for storing data that are to be transferred to or received from the ISDN-based bus.

18. (new) The interface of claim 17 wherein the control unit comprises a control register block (CRB) coupled to the processor bus for receiving control information for programming the interface, wherein based on the information, the appropriate port, time slots and direction are selected for data transfer.

19. (new) The interface of claim 17 wherein the data transfer unit further comprises an interface buffer (IB) coupled to the PBIS and IBIS, the IB provides intermediate buffering of data between the PBIS and IBIS blocks.

20. (new) The interface of claim 19 wherein the IB comprises a plurality of register banks, each register bank comprising a plurality of registers to form a register stack.

21. (new) The interface of claim 19 wherein the IB includes first and second register banks for each data port, wherein each register bank comprises a plurality of registers to form a register stack.

22. (new) The interface of claim 9 wherein the control unit comprises a control register block (CRB) coupled to the processor bus for receiving control information for

Appl. No. 10/065, 005

Amendment dated January 18, 2005

Amendment made in response to Office Action dated October 18, 2004

programming the interface, wherein based on the information, the appropriate port, time slots and direction are selected for data transfer.

23. (new) A method of transferring data between an ISDN-based bus which communicates in ISDN frames divided into a plurality of slots and a processor bus comprising:
- storing data to be transferred between the ISDN-based bus and the processor bus in a data transfer unit of an interface; and
  - transferring stored data between the ISDN-based bus and the processor bus, wherein the transferring of data is capable of accessing all slots of an ISDN frame.